

# OUTDOOR CABINET SYSTEM PRODUCTS

OUTDOOR STEEL CABINET TYPE A, B



## SPECIFICATIONS


A cabinet for outdoor installation Wall mounting. Surveillance equipment (CCTV) installed equipment stay. And fiber optic distribution, Industrial Media Converter. Industrial Ethernet Switches and has

## FEATURE


- Made by Electro galvanize steel thickness 1.0 mm. it does not rust and is lightweight Including green-yellow ground wire size 2.5mm.
- There are 4 gland audio cables to hold the cable and have a wire interconnected between Cabinet lid and cabinet to prevent short circuit current.
- The color of the cabinet for a special kind of external. Dark gray Through a color system with the painting process. Electro-static Powder Coating international standard ASTM.
- Front-door key lock Push Handle Lock Flush caps cabinet to increase security even more.
- Both sides Drilling ventilation fins And to protect the water in the aquarium.
- 2 mm. thick steel rear support for the cabinet to seize power pole.
- Roof rack can be mounted blower 4 "has two built-in cabinets can be cooled well. And help extend the useful life of the equipment inside the cabinet.
- Cover container and container roof with a rubber shield around the cabinet to prevent water from entering inside, using CNC Foam Gasket Technology.
- Inside pad (Plate) for lead 1.5 mm. Aladdin could removable for mounting to be installed inside the cabinet and build Din Rail mounting, Industrial Media Converter and Industrial Ethernet Switches.
- 3 hole perforated base cabinet size 3/4 inch and 1 inch for attaching to the cabinet
- Inside the cabinet there is a Cable Wire Guide for fixing the cables
- The plate has a Stud nut, can be installed in two layers (stacked) and has a plate to hold the Adapter snap Plate 2 Plate supports fiber optic up to 24 Core
- Ground connection cable between the cabinet and the lid of the cabinet.
- Can be ground wire, Splice tray, Cable Wire Guide, Cable Management, Surge and Breaker in cabinet and can install Power Bar.
- Have roof for rain protection.
- Fan x 2, 3



## MOUNTING OPTIONS



Pole Mount Bracket



Wall Mount Bracket

## STANDARD

- IP 55, IP 66.
- ISO 14001, ISO 9001

## ORDER INFORMATION

(Material: Panel)

- E = Electro Galvanized
- S = Stainless Steel
- A = Aluminium

(Dimension = H x W x D)

- A = 680 x 430 x 200 mm
- B = 740 x 500 x 250 mm

R - OD

XX

XX

XX

XX

- 10 = 1.0 mm
- 12 = 1.2 mm
- 15 = 1.5 mm
- 20 = 2.0 mm

└ 20 = 2.0 mm

(Front-door: Thick)

(Panel: Thick)

FOCOMM (THAILAND) CO., LTD

12 Soi Sukhaphiban 5 Soi 5 Yaek 3, Tha Raeng Subdistrict, Bang Khen District Bangkok 10220

Email : info@focomm-cabling.com www.focomm-cabling.com

