

SURGE PROTECTOR PRODUCT

C Class Single Phase AC Power Surge Protective Device



FEATURES




- Thermal disconnect device
- High current capacity, quick response
- Low residual voltage, free of leakage current
- Remote warning
- 40kA maximum surge current
- 50/60Hz 385V, Protection mode: L/N-PE
- Easy installation with Din rail mounting
- Status indicators visually verify protection level
- Plug connectors for quick and easy connection or rewiring
- There is a circuit to prevent interference (EMI).
- There is a function to turn on and off the display of the device.

APPLICATIONS



- Protection of C class AC Power System
- Protection of power distribution system
- Protection of terminal devices
- Sensitive electronic equipment
- Telecom centers
- Automatic control centers
- Intelligent buildings
- Industrial enterprises
- Medical institutes
- CCTV, Solar Cell



Dimensions



Wiring Diagram



SPECIFICATIONS

Model	SP-PC40-385/2
Nominal operating voltage Un	220/380VAC
Maximum continuous operating voltage Uc	385VAC
Nominal discharge current In (8/20µs)	20KA
Maximum discharge current I _{max} (8/20µs)	40KA
Protection level Up (8/20µs,20KA)	≤1.5KV - ≤1.7KV
Response time Ta	≤25ns
Protection modes	4:L1/L2/L3/N-PE 3+N:L1/L2/L3-N,N-PE 2:L/N-PE 1+N:L-N,N-PE
Front circuit breaker	63A
Delay system for supplying electricity	2 sec
Dimension	90*36*65mm
Weight	250-1200g
Mounting type	DIN rail : 35mm
Housing material	Anti-flaming
Index of protection	IP20
Operating environment	Temperature:-40-+85°C humidity: ≤95%
Remote control (optional)	Normally closed, normally open or COM
warranty	3 year warranty
Work Status	Green:ok Red:defect
Standards Compliance	IEC 61312-1, IEC 61312-3 (pending),IEC 61024-1, IEC 61000-4-5, IEC 61643-1-1 , IEC 61643-1-2 (pending), IEC 62066 (pending), IEC 61643-2-1 (pending), IEC 61643-1, NFC 61740, VDE 0675, UL 1449, BS 6651 ,ROHS, ISO9001,EN/IEC61643-11:2011,IEE C62-41-1991, FCC, Ce